

ELEVATE™ PLATFORM SYSTEM



The **ELEVATE™ Platform System** is a lightweight and portable deck that allows cultivators to access Pipp's Multi-Tier Mobile Grow Racks quickly, efficiently, and most importantly - safely. This patented system was designed to integrate with Pipp's Bulk Rack Shelving Systems without any modifications. The ELEVATE™ Platform System can be installed on new or existing mobile vertical grow racks. Pipp offers design services to customize your ELEVATE™ System to fit your mobile vertical grow racks.

FEATURES:

- ▶ Quick and simple setup.
- ▶ Lightweight components allow one person to set up the entire system.
- ▶ Aluminum and galvanized steel components provide great corrosion resistance.
- ▶ Deck sections are 22" by 49" for use in any layout.
- ▶ 22" wide walkway gives ergonomic access to canopy without giving up overall canopy throughout the room.
- ▶ Multiple people can access and work on the platform at once.
- ▶ Galvanized steel support rails hold 650 lbs per pair (tested to 4x capacity per OSHA requirements).
- ▶ Support rails are adjustable on 2" increments to give full flexibility in selecting platform heights and create the most ergonomic working area.
- ▶ Rails have integrated anti-dislodge protection features to keep beams secure while in use.
- ▶ Ladders available to accommodate deck heights between 30" and 120" A.F.F.
- ▶ If the mobile aisle is 46" or larger, two separate working rows of the patented ELEVATE™ Platform System can be used simultaneously.

SYSTEM SPECIFICATIONS

DECKS

- ▶ Decks are 22" x 49".
- ▶ Engineered to work with 325 lb capacity per deck.
- ▶ Weigh less than 10 lbs.
- ▶ "Daisy-chain" and ladder attachments integral to each deck.
- ▶ Marine-grade aluminum for corrosion resistance and weight reduction.

RAILS

- ▶ Galvanized steel rails for corrosion resistance and strength.
- ▶ 650 lbs capacity.
- ▶ Available in 96" and 48" sections.
- ▶ Anti-dislodge tabs secure rails in place.
- ▶ Accommodates end-of-aisle deck stops.

LADDERS

- ▶ Lightweight aluminum tube construction.
- ▶ 250 lbs capacity.
- ▶ Range from 3-rung to 10-rung to cover any deck height from 30" to 120" A.F.F.
- ▶ 3 position hook plates give multiple angle options.
- ▶ Anti-dislodge slots secure the ladder to the end platform for safe and secure placement of the ladder.

*OSHA safety guidelines may vary by state. It is the responsibility of the facility to adhere to the safety guidelines for their state.